

Steady Brand Music Player

Plug + Play

Follow these simple steps to set up your pre-tuned music player with your existing audio system and network.

IN THE BOX

- Music player
- Ethernet cable
- 5V power supply
- RCA audio cables

1

ETHERNET

Connect to the Internet

Use the ethernet cable to connect the music player to your internet connection or router (LAN port).

2

AUDIO

Connect to the Amplifier

RCA cable from output A (or B) on the player to the AUX / CD input on your amplifier or amplified speaker.

3

POWER

Connect to Power

Plug the supplied 5V adapter into the DC jack. The unit powers on automatically.

FRONT PANEL



THAT'S IT

The player begins playing audio about 90 seconds after power-up, and the song title and artist appear on the front-panel display.

Rear Panel & Specs

REAR PANEL CONNECTIONS



A/B

RCA analog audio out

LAN

RJ-45 Ethernet port

DC

5V power input

Zones

One stereo or dual mono

DIMENSIONS & POWER

Size (W×H×D)	5.75" × 1.25" × 3.25"
Weight	0.5 lbs (with supply)
Power supply	In 100–240V · Out 5V / 2A
Operating temp	0–55°C (32–131°F)

ANALOG AUDIO OUTPUTS

Outputs	2× RCA (stereo or dual mono)
Full-scale output	2 VRMS · 10 kΩ load
Dynamic range	93 dB · THD+N –86 dB
Frequency resp.	±0.1 dB, 25 Hz–20 kHz

NETWORK ALLOWANCES

PORTS

80

443

Outbound HTTP / HTTPS

DOMAINS TO ALLOW

- *.kalipsocontrol.com
- *.customchannels.net
- *.customchannels.rocks

The player uses outbound sessions only. DHCP or Static addressing supported.

TECH SUPPORT

support@steadybrand.com

EMAIL

greg@steadybrand.com